

POWERPACK 3K

GENERAL SPECIFICATIONS

CINE-ACS-LUM-114

Nominal battery capacity	2880 Wh / 60 Ah	Lithium Ion
Maximum output	3000 VA	2x connector NF 16 A
Adjustable input voltage	From 90 to 280 VAC 50/60 Hz	Powercon Connector Input protection 16 A
Regulated output voltage	230 VAC \pm 5%	Pure sinusoidal battery mode
Output frequency	50 Hz or 60 Hz	Pure sine wave
Output protection	16 A	Differential protection 30 mA
Charging time	2 hours at 30 A	60 A maximum
Adjustable charging current	From 1 A to 60 A	30 A maximum on household plug
Bypass transfer time	10 ms (UPS, VDE)	20 ms (APL)
Performance	> 90%	Performance if plugged > 95%
USB port	30 W maximum	2x USB-A port
Operating temperature range	From 0°C to 55°C	From 32°F to 131°F
Storage temperature range	From -15°C to 60°C	From 5°F to 140°F
Humidity range	From 5% to 95%	Without condensation
IP (Ingress Protection)	IP42	/
Dimensions	307 * 466 * 604 mm (L * W * H)	12 * 18 * 23" (L * W * H)
Weight	34 kg	75 lbs

