

POWERPACK 5K

GENERAL SPECIFICATIONS

CINE-ACS-LUM-115

Nominal battery capacity	5760 Wh / 120 Ah	Lithium Ion
Maximum output	5000 VA	Maximum coupling: 15000 VA
Adjustable input voltage	From 90 to 280 VAC 50/60 Hz	1x connector 32/50 "Marechal"
Regulated output voltage	230 VAC \pm 5%	2x connector NF 16 A 1x connector 32/50 "Marechal"
Output frequency	50 Hz or 60 Hz	Pure sine wave
Output protection	25 A	Differential protection 30 mA
Charging time	2 hours at 60 A	60 A maximum
Adjustable charging current	From 1 A to 60 A	16 A maximum on household plug
Bypass transfer time	10 ms (UPS, VDE)	20 ms (APL)
Performance	> 90%	Performance if plugged >95%
Sockets	IN: 1x CEE 17 - 32 A - Single phase (P17 or Marechal®)	OUT: 2x Schuko 16 A 1x CEE 17 - 32 A - Single phase (P17 or Marechal®)
USB port	30 W maximum	2x USB-A ports
Operating temperature range	From 0°C to 55°C	From 32°F to 131°F
Storage temperature range	From -15°C to 60°C	From 5°F to 140°F
Humidity range	From 5% to 95 %	Without condensation
IP (Ingress Protection)	IP45	/
Dimensions	605 * 680 * 766 mm (L * W * H)	23 * 26 * 30" (L * W * H)
Weight	85 kg	176 lbs

